

CONTINUATION IN PART

Application Based on

Docket **83072ASLP**

Inventors: William C. Wendlandt and Daniel N. Peek

Customer No. 01333

**STORAGE PHOSPHOR CASSETTE**

Commissioner for Patents,  
ATTN: BOX PATENT APPLICATION  
Washington, D. C. 20231

Express Mail Label No.: **EL486846697US**

Date: August 6, 2001

## **STORAGE PHOSPHOR CASSETTE**

### **CROSS REFERENCE TO RELATED APPLICATION**

This is a continuation-in-part of application Serial No. 09/896,697,  
5 filed June 29, 2001 entitled " STORAGE PHOSPHOR CASSETTE " by  
Wendlandt et al.

Reference is made to commonly assigned application U.S. Serial  
No. 09/896,735, entitled "A STORAGE PHOSPHOR CASSETTE HAVING A  
CORNER ELEMENT", and filed on common date herewith in the names of  
10 Wendlandt et al., and which is assigned to the assignee of this application.

Reference is made to commonly assigned application U.S. Serial  
No. 09/896,625, entitled "STORAGE PHOSPHOR CASSETTE", and filed on  
common date herewith in the names of Wendlandt et al., and which is assigned to  
the assignee of this application.

15

### **FIELD OF THE INVENTION**

The present invention relates generally to cassettes for  
photographic elements, and more particularly, to an x-ray cassette used in  
computed radiography.

20

### **BACKGROUND OF THE INVENTION**

In the field of computed radiography, a photographic element has  
an image formed thereon by x-rays. The photographic element is subsequently  
provided to a reader wherein the element is stimulated to emit a radiation pattern  
25 that is indicative of the image formed by the x-rays. Typically, storage phosphors  
are used to capture radiographic images from incident x-rays. Most radiographic  
procedures are carried out within normal room lighting conditions, accordingly, a  
primary requirement for any computed radiography x-ray cassette is to shield the  
storage phosphor from exposure by ambient light.

Cassettes of the kind used in computed radiography may comprise a container having an upper and lower parts that are hinged together so that they can be opened for insertion of a flexible film sheet or a rigid film plate comprising the photographic element. The cassette is closed and latched so that  
5 the cassette with the element therein can be used with an x-ray apparatus to produce an image on the photographic element. Then, the cassette is taken to a reader where the cassette is opened and the photographic element extracted by suitable feeders, such as a suction feeding device. The photographic element separates from the cassette, and is transported through the reader where it is  
10 stimulated to emit a radiation pattern which is captured for storage and use. The radiation pattern is subsequently erased from the photographic element before being returned to the cassette for re-use.

U.S. Patents No. 5,861,631 (Wendlandt et al.),  
5,869,839 (Wendlandt et al.), and 5,943,390 (Wendlandt et al.), commonly  
15 assigned and incorporated herein by reference, disclose cassettes of the kind used in computed radiography.

While such cassettes may have achieved certain degrees of success in their particular applications, cassettes are susceptible to various types of damage when dropped or roughly handled. Accordingly, it is desirable to  
20 increase the durability of the cassette while minimizing cost and weight, and preserving the same basic nature of design.

Accordingly, a need continues to exist for a cassette which is durable and reduces its susceptibility to damage when dropped or roughly handled, and the same basic nature of design is preserved.

## SUMMARY OF THE INVENTION

An object of the present invention is to provide a cassette which has increased durability, and is resistant to damage when dropped or roughly handled.

This object is given only by way of illustrative example. Thus, other desirable objectives and advantages inherently achieved by the disclosed invention may occur or become apparent to those skilled in the art. The invention is defined by the appended claims.

5           According to one aspect of the invention, there is provided a x-ray cassette comprising a shell and a storage phosphor assembly. The shell comprises an upper and lower panel, a first and second side member, and a front end member. The first and second side members and front end member join the upper and lower panels to define a cavity having an open end. The storage phosphor  
10 assembly comprises a back end member, an insert plate, and an edge insert. The storage phosphor assembly is adapted to be removably contained within the shell such that the back end member closes off the open end of the shell. A first side of the edge insert is affixed to the insert plate. A first end of the edge insert is disposed adjacent the back end member, and a second end of the edge insert  
15 comprises at least one recess on the first side. In a preferred embodiment, the second end of the edge insert comprises a plurality of spaced recesses. In a preferred embodiment, the insert plate includes a honeycomb core comprising honeycomb cells wherein the honeycomb cells disposed along a perimeter of the honeycomb core are filled with an adhesive or epoxy.

20           The present invention provides a cassette which has increased durability and reduced susceptibility to damage when dropped or roughly handled.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

25           The foregoing and other objects, features, and advantages of the invention will be apparent from the following more particular description of the preferred embodiments of the invention, as illustrated in the accompanying drawings.

FIG. 1 shows a perspective view of a storage phosphor cassette in accordance with the present invention.

30           FIG. 2 shows a bottom view of the cassette of FIG. 1.

FIG. 3 shows a top view of the storage phosphor assembly of the cassette of FIG. 1.

FIG. 4 shows a side view of the storage phosphor assembly of FIG. 3.

5 FIG. 5 shows a bottom view of a corner of the cassette of FIG. 2.

FIG. 6 shows a perspective view of a corner of the cassette of FIG. 2.

FIG. 7 shows a cross sectional view of the insert plate of the storage phosphor assembly of FIG. 3 taken along the plane of the insert plate.

10 FIG. 8 shows a top view of a corner of the insert plate of the storage phosphor assembly of FIG. 3.

FIG. 9 shows a top view of another corner of the insert plate of the storage phosphor assembly of FIG. 3.

15 FIG. 10. shows a cross sectional view of insert plate of the storage phosphor assembly of FIG. 3 taken transverse to the plane of the insert plate.

FIG. 11 shows a perspective view of a corner of the of insert plate of the storage phosphor assembly.

FIG. 12 shows a perspective view of another corner of the insert plate of the storage phosphor assembly.

20 FIG. 13 shows a perspective view of the back end member of the storage phosphor assembly.

FIG. 14 shows an edge insert of the storage phosphor assembly in accordance with the present invention.

25 FIG. 15 shows a storage phosphor assembly incorporating the edge insert of FIG. 14.

FIG. 16 shows an edge insert illustrating various recess configurations.

## DETAILED DESCRIPTION OF THE INVENTION

The following is a detailed description of the preferred embodiments of the invention, reference being made to the drawings in which the same reference numerals identify the same elements of structure in each of the  
5 several figures.

Figures 1-4 show a storage phosphor cassette 10 in accordance with the present invention. Cassette 10 includes a shell 12 comprising an upper panel 14, a lower panel 16, a first side member 18, a second side member 20, and a front end member 22. Upper and lower panels 14,16 are preferably rectangular  
10 in shape. First side member 18, second side member 20, and front end member 22 join upper and lower panels 14,16 to form a five-sided cavity having an open end 24.

Cassette 10 further includes a storage phosphor assembly 26 having a front edge 27, a back end member 28, an insert plate 30 having an upper  
15 face and being cantilevered from back end member 28, and a storage phosphor 32 disposed on the upper face of insert plate 30. A front edge of insert plate 30 includes corners 68,70, which are preferably rounded. Back end member 28 includes apertures 29,31 for access to the interior of back end member 28 to latch and unlatch a latch bar 50 slidably mounted therein.

20 Storage phosphor assembly 26 is removably contained within the cavity of shell 12 such that back end member 28 of storage phosphor assembly 26 closes off open end 24 of shell 12, thereby providing a light-tight enclosure for storage phosphor 32.

Back end member 28 of storage phosphor assembly 26 includes  
25 end portions 64,66. First and second side members 18,20 include a corner structure 60,62, respectively, which respectively engage end portions 64,66. Corner structures 60,62 can be integral with first and second side members 18,20, or as illustrated, can be separate corner pieces which are secured to first and second side members 18,20. End portions 64,66 and respective corner structures  
30 60,62 have complimentary, interlocking configurations, such that, should cassette

10 be dropped and a force exerted on either corner structure 60,62, the force is transferred to storage phosphor assembly 26, forcing assembly 26 into shell 12. Corner structure 62 engaged with end portion 66 is further illustrated in Figures 5-6.

5 Referring now to Figures 7-10, to minimize damage to insert plate 30 should cassette 10 be dropped, insert plate 30 is comprised of a lightweight rigid structure including an aluminum honeycomb core 71 and outer aluminum skins 72,74. The edge of honeycomb core 71 is milled out (recessed) around the entire perimeter to create a cavity. As best illustrated in Figure 7, edge inserts 10 76,78,80 are each glued into a side of the cavity formed in the honeycomb structure. Back end member 28 is inserted to a fourth side of the cavity formed in the honeycomb structure. One end of edge insert 76 interlocks with back end member 28 by means of a connector 90 which can be, for example, a key or leg. Similarly, one end of edge insert 80 interlocks with back end member 28 by 15 means of a connector 92 which can be, for example, key or leg. As illustrated in Figure 7, connectors 90,92 are each shown as a leg of back end member 28 extending into edge inserts 76,80 in a direction parallel to the length of back end member 28, which is transverse to the length of edge inserts 76,80, respectively. The interlocking arrangement of edge inserts 76,80 with back end member 28 20 transfers a force from a side impact to cassette 10 to back end member 28 rather than buckling outer aluminum skins 72,74.

Referring now to Figures 11-12, edge inserts 76,80 may optionally comprise a plurality of shallow slots or channels 93 disposed on at least one of its surfaces. Such channels 93 promote adhesion of the edge inserts with insert plate 25 30 since they provide additional surface area for the glue to migrate and adhere rather than being directed to the cells of the honeycomb. As illustrated, channels 93 form an angled relative to an edge of edge inserts 76, 80. A cross-hatch pattern might also be employed.

As illustrated in Figures 11-13, back end member 28 may also optionally comprise channels 93, with channels 93 being angled relative to an edge of back end member 28.

Preferably, edge inserts 76,80 extend slightly beyond the perimeter of outer aluminum skins 72,74 (as shown in Figure 3 at 94,96, respectively) thereby creating a shock absorption system to absorb and distribute forces on insert plate 30. If edge inserts 76,80 extend beyond the perimeter of outer aluminum skins 72,74, then preferably channels 93 are disposed on that portion of edge inserts 76,80 which do not extend beyond the perimeter, but rather, are disposed on that portion of edge inserts 76,80 internal to honeycomb core 71.

Preferably, edge inserts 76,80 are of aluminum, edge insert 78 is of a polymeric material, and back end member 28 is of an aluminum material.

Referring now to Figures 14 and 15, one side of edge inserts 76,80, (the side to be inserted into insert plate 30, i.e., the side glued into the side of the cavity formed in honeycomb core 71) may comprise a non-planar configuration. That is, a side of edge inserts 76,80 may include at least one groove or recess 100. Recess 100 is disposed at the end of edge inserts 76,80 adjacent edge insert 78. Accordingly, when edge insert 76 or 80 is inserted into insert plate 30, recess 100 promotes adhesion of the edge inserts with insert plate 30 since recess 100 provides additional surface area for the glue to migrate and adhere.

Further, any exposed (i.e, partially or fully open) cells of honeycomb core 71 disposed along the perimeter of honeycomb core 71 are preferably filled with an adhesive or epoxy material which also fills recesses 100 of edge inserts 76,80. The addition of the hardened adhesive or epoxy provides increased stiffness to the edge of honeycomb core 71. A filler material other than adhesives and epoxys might be employed to fill the cavities of the cells to provide compressive support structure, for example, liquid materials which harden when cured, adhesives, sealants, surface fillers, potting or encapsulating compounds, and expanding foams. Examples of adhesives include epoxy adhesives, methacrylate adhesives, urethane adhesives, and hot melt adhesives. Examples of



sealants include silicone sealant, urethane sealant, polysulfide sealant, and acrylic caulk. Examples of surface fillers and potting compounds include polyester resin with talc powder, epoxy resin with silica, polymeric putties and resin systems. Examples of expanding foams include two-part liquid expanding urethane foam.

- 5 If any of these materials include adhesive characteristics, the materials will promote adhesion between the edge inserts with the insert plate in addition to providing structural support.

The stiffness of the edge of honeycomb core 71 is further enhanced since the linear path for bending/buckling has been reduced/eliminated. That is,  
10 there is no longer a linear path for bending or buckling to occur between edge inserts 76,80 and honeycomb core 71, in the event of an impact force or rough handling to cassette 10. Should cassette 10 experience an impact force, the impact force would be directed along the non-linear path where the adhesive (filler material) interfaces to either honeycomb core 71 or recesses 100 in edge  
15 inserts 76,80, and since there is no linear path, the likelihood of bending or buckling is reduced/eliminated. Stated alternatively, should cassette 10 experience an impact force, the additional material filling honeycomb core 71 in conjunction with the non-linear interfaces of the adhesive/epoxy to both honeycomb core 71 and recesses 100 in edge inserts 76,80, reduce/eliminate the likelihood of bending  
20 or buckling in that location since the linear interface has been removed, the linear interface being the area likely to fail (i.e., prone to failure).

A plurality of recesses 100 may be employed in each edge insert 76,80 as illustrated in Figures 14 and 15 wherein five recess 100 are employed with an interstice 102 therebetween.

- 25 Applicants have noted that five or six recesses 100 may be suitable for the present application with each recess 100 comprising a semi-circular shape having a radius of 0.5 inches and interstice 102 of 0.080 inches. However, those skilled in the art will recognize that other shapes for recess 100 may be suitable. For example, as illustrated in Figure 16, recess 100 may comprise a wave, oval,  
30 skewed curve, or a linear shape such as a triangle. Fewer or more recesses 100

may be employed than that illustrated in Figures 14 and 15. Similarly, interstice 102 may be greater or smaller than that illustrated.

The invention has been described in detail with particular reference to a presently preferred embodiment, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention. The presently disclosed embodiments are therefore considered in all respects to be illustrative and not restrictive. The scope of the invention is indicated by the appended claims, and all changes that come within the meaning and range of equivalents thereof are intended to be embraced therein.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000

## PARTS LIST

10	cassette
12	shell
14	upper panel
16	lower panel
18	first side member
20	second side member
22	front end member
24	open end
26	storage phosphor assembly
27	front edge
28	back end member
29,31	apertures
30	insert plate
32	storage phosphor
50	latch bar
60,62	corner structures
64,66	end portions
68,70	front corners
71	honeycomb core
72,74	outer aluminum skins
76,78,80	edge inserts
90	connector
92	connector
93	channels; slots
94,96	extensions
100	groove; recess
102	interstice